



			Slip Resistance			
	Standard	Result	Product	Size (mm)	DIN 51130	DIN 51097
		See separate table	MLC01	406,4 X 406,4	R9	A
		2,5 mm	MLC07	406,4 X 406,4	R10	B
		0,55 mm	MLC08	406,4 X 406,4	R10	B
		Kguard+ PU coating	MS1	304,8 X 304,8	R10	C
<b>Guarantee</b>	Light industrial	10 year	MS2	304,8 X 304,8	R10	C
	Commercial	12 year	MS3	304,8 X 304,8	R10	C
	Domestic	15 year	MS4	304,8 X 304,8	R10	C
		No	MS5	381,0 X 381,0	R10	C
	EN 649	Heterogeneous PVC	MX92	304,8 X 304,8	R10	C
	EN 685- Light industrial	41:Light industrial moderate	MX93	304,8 X 304,8	R10	C
	EN 685- Commercial	32: Commercial general	MX95	304,8 X 304,8	R10	C
	EN 685- Domestic	23: Domestic heavy	MX97	304,8 X 304,8	R10	C
	EN 13501-1	B <sub>fl</sub> -s1	MX98	304,8 X 304,8	R10	C
	EN ISO 9239-1	Pass				
	EN ISO 11925-2	Pass				
	EN 423	Class 0				
	EN ISO 105-B02	≥6				
	EN 660-2	Group T				
	EN 434	≤ 0.25%				
	EN ISO 717-2 / EN ISO 140-8	ΔL <sub>w</sub> = 2 db				
	EN 1815	Pass				
	EN 433	≤ 0.1mm				
	EN 425	Pass				
	EN430	4090 g/m <sup>2</sup>				
	ISO 8302	0,0120 m <sup>2</sup> K/W				
		Suitable for underfloor heating. Max 27°C				
	DIN 51130	See separate table				
	DIN 51097	See separate table				
	EN 13893	DS				
	NF EN ISO 1600	A+ (<250µg/m <sup>2</sup> )				
	Universal	Yes				
	Acrylic	Yes				
	Epoxy	Yes				
	High Temperature	Yes				
	Pressure sensitive	Yes				
		Suitable				



For more information:  
 T: +44 (0)1386 820105  
 F: +44 (0)1386 820132  
 info@designflooring.com