

	Standard	Result	Product	Size (mm)
Size		See separate table	CRT4301	307 x 600
Thickness	ISO 24346	6,5 mm	CRT4302	307 x 600
Wear layer	ISO 24340	0,55 mm	CRT4303	307 x 600
Surface treatment		PU coating	CRT4304	307 x 600
Guarantee	Commercial	12 years	CRP4501	1220 x 179
	Domestic	Lifetime warranty	CRP4503	1220 x 179
Bevelled edge		No	CRP4504	1220 x 179
Mass per unit area	ISO 23997	8 046 g m ⁻²	CRP4506	1220 x 179
Standards	ISO/DIS19322.2:2016	Heterogeneous PVC + backing	CRP4507	1220 x 179
		Type I	CRP4508	1220 x 179
Classification	ISO 10874 Commercial	32:-commercial general	CRP4509	1220 x 179
	ISO 10874 domestic	23:-Domestic heavy	CRP4510	1220 x 179
Reaction to fire	EN13501-1	B _{fl} -s1		
Dimensional stability	BS EN ISO 23999 (60 °C)	≤0,15%		
Acoustic impact noise reduction	EN ISO 140-3	ΔL _w = 19 dB*		
	EN ISO 140-3	ΔL _{LIN} = 11 dB		
Indentation-residual	ISO 24343-1	≤0,1 mm		
castor chair continuous use	ISO 4918	pass 25 000 cycles		
Thermal resistance	ISO 8302	0,052 m ² K/W		
		suitable for underfloor heating max 27 °C		
Slip resistance**	EN 13893	DS		
	DIN 51130	R10		
VOC emission	French VOC regulation (ISO 16000)	A+		
Adhesive		None required; please install according to our installation instructions.		
Recycling		Suitable		
Phthalate free				

* This result is subject to confirmation in independent laboratory testing

**slip resistance is measured on ex-factory product. Slip resistance in use will be affected by surface contamination and by how the product is maintained

For more information:

Designflooring - T: +44 (0)1386 820105 | F: +44 (0)1386 820132

Designflooring SAS - T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH - T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland - T: 020 200 8282 | F: 020 200 8386

e: info@designflooring.com

www.designflooring.com



Manufactured to ISO9001



PALIOCORE