

# LINOWALL technical data

CERTIFICATION & CLASSIFICATION	STANDARDS	LinoWall 2 mm
Type of floor covering	ISO 24011 (EN 548)	Approved linoleum for walls application
CE certification	EN 15102	yes
TECHNICAL CHARACTERISTICS	STANDARDS	
Surface treatment		xf <sup>2</sup> <sup>TM</sup>
Total thickness	EN ISO 24346 (EN 428)	2.0 mm
Total weight	EN ISO 23997 (EN 430)	ca. 2 900 g/m <sup>2</sup>
Form of delivery	EN ISO 24341 (EN 426)	≤ 16 x 2 m
TECHNICAL PERFORMANCES	STANDARDS	
Fire classification	EN 13501-1	Bs2 d0
Fire effluent toxicity	ISO 5659-2 (evaluation according to EN 45545-2 Annex C)	ClTg(4min.) = 0,06 and ClTg(8min.) = 0,09, testing with irradiance of 50 kW/m <sup>2</sup> without pilot flame
Static electrical propensity	EN 1815	< 2 kV
Impact resistance	EN 259-2	Resistant to impacts
Chemical resistance	EN ISO 26987	Resistant to dilute acids, oils, fats, current solvents and alkalis
Thermal resistance	EN ISO 10456	0.018 m <sup>2</sup> K/W
Light fastness	EN ISO 105-B02	≥ 6
Presence of phthalate compounds	CEN ISO/TS 16181	Phthalate free
Odor test requirement of emission class M1	EN ISO 16000-28 i.A., VDI 4302	Meets requirement
Spongeability, washability and extra washability	EN 12956 EN 233	Extra washable
Determination of antibacterial activity	ISO 22196	Naturally bactericidal (Bacteria mix - EColi and MRSA)
Colours		6



The above information is subject to modification for the benefit of further improvement. (02/17).

**DISCLAIMER:** Although the utmost care is taken, the data here given could differ and be subject to modifications from a technical point of view.

In its strive to improve its floor solutions, Tarkett reserves the right to modify its technical specifications, colours and materials at any moment and without prior notice. Please, check the effective availability of the products presented at the time of order. Due to the technical limits of reproduction and printing techniques used, the appearance (colour) of the product may vary from the samples, panels or other visual display materials exhibited to the customer. It is mandatory to have the products installed properly if they are to service correctly and safely. Refer to Tarkett technical installation and maintenance directions, available at [www.tarkett.com](http://www.tarkett.com) or at your Tarkett dealer.

CUSTOMS TARIFF : 482050000000F

## SUSTAINABILITY


Tarkett was the first linoleum flooring manufacturer to be Cradle to Cradle® certified - underlining our strong commitment to sustainability.

## Product certifications



All our linoleum ranges (except Silencio 18dLinoleum, SD Static Dissipative xf<sup>2</sup> and Linoleum Conductive xf<sup>2</sup> ranges)

## International certifications



\*Information sur le niveau d'émission de substances volatiles dans l'air extérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



## Factory certifications



All our linoleum products are eligible for LEED v4 credits. For more information: <http://www.c2ccertified.org/products/registry>