























Altro ContraX™

Altro ContraX™ is a heterogeneous slip-resistant, resilient safety floor. It is a dense and impermeable PVC safety floor with an EasyClean surface and an integral bacteriostat to ensure hygiene and a permanent anti-bacterial performance. Altro ContraX contains silicon carbide and quartz granules on the surface.
www.altro.com

Altro ContraX™ es un pavimento de seguridad de PVC flexible, de 2 mm de espesor. Este pavimento de PVC denso e impermeable tiene un tratamiento Easyclean y agente bacteriostático para garantizar la higiene, fácil limpieza, y un perfecto comportamiento anti-bacterias. Altro Contrax contiene carburo de silicio y partículas de cuarzo en su superficie. www.altroscandess.es

Altro ContraX™ ist ein 2,0 mm dicker, heterogener, richtungsfreier Sicherheitsbodenbelag aus PVC mit in der gesamten Nutzschiicht eingestreutem Siliziumcarbid und Quarzen auf der Oberfläche. Die dichte und wasserundurchlässige EasyClean Oberfläche beinhaltet zusätzlich ein integriertes Biozid für eine hygienische und permanent antibakterielle Leistung. www.altro.de

| | | | |
|--|---|---|--|
| Colours Colores Farben | 12 | | |
| Flooring Type Tipo de pavimento Belagsart |   | EN 13845/ EN 13553 | Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag |
| Classification for use Areas de uso Einsatzbereiche |   | EN 685 | 34 & 43 34 y 43 34 & 43 |
| Slip Resistance Resistencia al deslizamiento Rutschsicherheit |   | TRRL EN 13845 EN 13893 DIN 51130 | ≥ 36 ESf DS R10 |
| Thickness Espesor Total Gesamtdicke |  | EN 428 | 2 mm |
| Wear Layer Capa de uso Nutzschicht |  | EN 429 | 0.9 mm |
| Flexibility Flexibilidad Flexibilität |  | EN 435 | Pass Conforme bestanden |
| Weight Peso Flaechengewicht |  | EN 430 | 2.2 kg/m ² |
| Roll Dimensions Dimensiones del rollo Rollenabmessungen |   | EN 426 | 2.0m x 20.00m - 40m ² |
| Light Fastness Resistencia a la luz Lichtechtheit |  | EN 20105-B02 | ≥6 |
| Sound Insulation Aislamiento acústico Trittschal |  | ISO 140-8 | 4 dB |
| Wear Resistance Abrasión Verschleißverhalten |  | EN 13845 | ≤10% particles lost over 50000 Cycles ≤10% de las partículas perdidas en 50.000 ciclos ≤10% Parkittel werden über 50000 Umdrehungen verloren |
| Indentation Punzonamiento Resteindruck |  | EN 433 | ≤ 0.10mm |
| Fire Performance Reacción al fuego Brandverhalten |  | EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 | Class Bfl-s1 ≥8kW/m ² Pass Clase Bfl-s1 ≥8kW/m ² Conforme Klasse Bfl-s1 ≥8kW/m ² bestanden |
| Chemical Resistance Resistencia a los productos químicos Chemikalieneinwirkung |  | EN 423 | Good Buena beständig |
| Castor Chair Abrasion Huellas de sillas de ruedas Stuhlrollenbeanspruchung |  | EN 425 | Pass Conforme geeignet |
| Under floor heating Calefacción por el suelo Fußbodenheizung |  | EN 12667 | Suitable Apto geeignet |
| Electrical Behaviours Caraterísticas eléctricas Elektrisches Verhalten |  | EN 1815 | ≤ 2kV Antistatic ≤ 2kV Antiestáticas ≤ 2kV antistatisch |
| VOC Emissions Emisiones de VOC VOC Emissionen |  | prEN 15052 Section 01.350 AgBB/DiBt | Low/Pass/Approved Baja/Conforme/aprobado gering/geeignet/zugelassen |